

UVC MULTI ULTRAVIOLET SYSTEMS



Standard Features

- 304 SS Stainless Steel Body
- Mirror polished surface
- IP54 control panel
- Electronic card for each lamp
- High quality quartz sleeve for each lamp
- Time Counter
- 9000 hours lamp life
- Electricity supply 220- 230 V/ 50- 60 Hz
- 2- 7 bar operating pressure
- 2- 45 °C operating temperature

Design Criterias

- Temperature 20 °C
- Clear appearance
- Fe < 0,2 mg/L
- Mn < 0,05 mg/L
- TDS < 10 mg/L
- Transmission rate % 95

Optional Features

- 316 SS Stainless Steel Body
- 16 bar resistant design
- Beam sensor monitor
- Flanged connection



TECHNICAL FEATURES

CODE	MODEL	FLOW RATE m ³ /h 30.000u W/cm ²	FLOW RATE m ³ /h 40.000u W/cm ²	CONNECTION Inch	LAMP Qty	LAMP Watt
MM.UV5016	UVC 80 S	12	9	1 1/2	2	150
MM.UV5018	UVC 120 S	18	14	2	3	225
MM.UV5020	UVC 160 S	23	18	2	4	300
MM.UV5026	UVC 390 S	35	28	2 1/2	6	450
MM.UV5028	UVC 520 S	46	37	3	8	600
MM.UV5030	UVC 780 S	70	55	4	12	900
MM.UV5032	UVC1040 S	93	74	4	16	1200